



Tyne / Roto Cultivator

Achat 70



Upto 40%
Faster Operation



50% More
Tyre Life



Low
Maintenance



Loosening,
Crumbling, Leveling



Upto 40%
Fuel Saving



Technical Data - Achat 70

Model	Achat 70 – 3/6	Achat 70 – 3/7	Achat 70 – 3/9
Working width (cm)	150	180	220
No of tynes	6	7	9
No of rows	3	3	3
Possible Working Depth (cms)*	8-24	8-24	8-24
Recommended Operational Speed (kmph)*	8-12	8-12	8-12
Appx. Weight without roller (kg)	180	215	260
Appx. Weight with Roller (kg)	300	360	440
Tractor Output	HP	40-55	50-65
	KW	30 - 41	37 - 48
45 - 56			

*The working depth & recommended operational speed depends on the type of share, soil condition & tractor output.

All specifications, dimensions and weights are subject to continuous technical development and are therefore not binding. The weight specifications always refer to the basic equipment, subject to change.

PERFECT ENGINEERING



Unique Design

The unique 3 row design of cultivator provides the opportunity to work on the field with lot of weeds / residues on the surface from the previous crop. The arrangement of tynes ensures good pulling line

Overload Security



Even where the share point is firmly caught under the stone, tree root or rock ridge, all the LEMKEN implements are protected against damage by an additional shear bolt device as standard. The new shear bolt can be easily & quickly replaced, thus the work will not suffer.

Higher Underframe Clearance

Achat has good clearance height of 65 cm and tynes arranged at 25 cm from each other for clog-free operation. With the result the same implement can be used from shallow to deep cultivation. All soil capillaries are broken preventing the soil from drying out.

Loosening, Mixing & Crumbling

Different variety of reversible shares with easy attachment for consistently good penetration and improved mixing for shallow working & better mixing & crumbling for optimum mixing & crumbling for deep loosening.



Three Point Linkage

The easy three point linkage arrangement along with height adjustable drawbar and multiple holes for top link attachment, make the implement perfect for any available tractor and minimize the pulling forces. Thus LEMKEN makes it easy for the farmer to simply match the system to variety of requirements.

Precise Working Depth

The Achat is equipped with 340 mm roller suitable to deliver the following benefits:- Precise depth control without spanner work. The adjustment is made with the pin in a series of holes at the rear of the machine efficient crumbling & reconsolidating of soil uniform distribution of residues & clog free operation the maintenance free sealed ball bearing guarantees the maximum service life.

Adjustable spacing of tynes

Tynes spacing of Achat 70 can be adjusted as per requirement of field operations. Besides tyne's positions, number of tynes can be added or removed as per requirement.

High Inter-tyne distance

Achat 70 comes with three beam structure with maximum distance in between them. Each tyne mounted on beam is placed 75 cm apart from each other, which allows maximum movement of crop residue without clogging of the implement.

LEMKEN India Agro Equipment Pvt. Ltd.

Plot No. D-59, MIDC, Butibori, Nagpur, Maharashtra, India-441108
Landline-0710 4285400 Mobile- 95455 01199 | Website- www.lemken.in
Email- lemkenindia@lemken.com | Email- Customercare.India@lemken.com

Dealer